

## DECLARATION OF PERFORMANCE

according to Regulation (EC) 305/2011

№ 4-1-1-CPR-2019

- |  |  |
|--|--|
| <p>1.Unique identification code of the product-type:</p> <p>2.Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4):</p> <p>3.Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:</p> <p>4.Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11 (5):</p> <p>5.Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):</p> <p>6.System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:</p> <p>7.In case of the declaration of performance concerning a construction product covered by a harmonised standard:</p> <p>8.Declared performance:</p> | <p>Area code 27 – roomheaters fired by wood pellet fuel (EN14785:2006)<br/><b>VITTORIA 8</b></p> <p>Serial № (see rating label on the product).</p> <p>Freestanding air pellet stove with firedoors closed intended for rooms heating</p> <p><b>Victoria-05 Ltd.</b><br/>1B Ivan Momchilov Str., 5100 Gorna Oryahovitsa<br/>Republic of Bulgaria, email: info@v05.bg</p> <p>-</p> <p>System 3</p> <p>Notification authority: <b>Kontrol 94 Ltd.</b><br/>2 Mladost Str., 5100 Gorna Oryahovitsa,<br/>Republic of Bulgaria, Notified Body: NB1879<br/>Test report: NB 1879-K-01-2018</p> |
|--|--|

<b>Harmonized technical specification</b>		EN 14785:2006 and CEN/TS 15883:2009	
<b>Essential characteristics</b>		Performance	
<b>Fire safety</b>			
Reaction to fire		A1	
Distance to combustible materials		Minimum distances, in mm sides=300, rear=300, front=800	
Risk of burning fuel falling out		Pass	
Emission of combustion products CO at 13% O <sub>2</sub> nominal heat output		0.0166 %	208 mg/m <sup>3</sup>
Emission of combustion products CO at 13% O <sub>2</sub> reduced heat output		0.0281 %	351 mg/m <sup>3</sup>
Surface temperature		Pass (operating tool)	
Electrical safety		Pass	
Cleanability		Pass	
Flue gas temperature at nominal heat output		T 125 C	
Mechanical resistance (to carry a chimney/flue)		NDP	
<b>Heat output</b>			
Nominal heat output		6.10 kW	
Room heating output		6.10 kW	
Water heating output			
<b>Energy efficiency</b>		η 87.76 %	
<b>Emission of combustion products at 13% O<sub>2</sub></b>			
	<b>nominal heat output</b>	<b>reduced heat output</b>	
PM [mg/m <sup>3</sup> ]	19.4 mg/Nm <sup>3</sup>	-	
NOx [mg/m <sup>3</sup> ]	137.44 mg/m <sup>3</sup>	133.79 mg/m <sup>3</sup>	
OGC [mg/m <sup>3</sup> ]	31.60 mg/m <sup>3</sup>	51.41 mg/m <sup>3</sup>	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

01.04.2019  
Gorna Oryahovitsa


  
 Manager: .....  
 (Dimitar Nenov)